

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Fix All High Tack

Reference nr: 231708

Unique identification code of the product-type

Fix All High Tack

Intended use or uses of the construction product

Sealants for facade for interior and exterior applications, intended for use in cold climate

Sealants used for sanitary applications

Sealants for pedestrian walkways for interior use

Name and contact address of the manufacturer as required pursuant to Article 11(5)

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

Authorised Representative

Not relevant

System(s) of assessment and verification of consistency of performance of the construction product, as set out in Annex V

System 3: for reaction to fire

System 3: for essential characteristics

Construction product in accordance with applicable harmonised specifications

EN 15651-1:2012: Type F-EXT-INT-CC 20HM

EN 15651-3:2012: Type XS2

EN 15651-4:2012: Type PW-INT

The notified body

The notified body IFT Rosenheim GmbH, NB 0757 has carried out Determination of the Product Type under system 3.

Declared Performance: EN 15651-1:2012

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10%	
Tensile properties at maintained extension after water immersion	NF	
Tensile properties at maintained extension at -30°C	NF	
Durability	Pass	

Conditioning: Method B

Test Substrate: aluminium, mortar

Declared Performance: EN 15651-3:2012

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-3:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10%	
Tensile properties at maintained extension after water immersion	NF	
Microbiological growth	2	
Durability	Pass	

Conditioning: Method B

Test Substrate: aluminium, glass

Declared Performance: EN 15651-4:2012

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-4:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Loss of volume	≤ 10%	
Tensile properties at maintained extension	NF	
Tear resistance	NF	
Tensile properties at maintained extension at -30°C	NF	
Durability	Pass	

Conditioning: Method B

Test Substrate: aluminium, mortar



The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by

Ing. W. Dierckx
Senior Technical Product Manager
Soudal NV- Belgium

CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Fix All High Tack



NB 0757

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium
20

Reference nr: 231708

EN 15651-1:2012

EN 15651-3:2012

EN 15651-4:2012

Sealants for facade for interior and exterior applications, intended for use in cold climate

Sealants used for sanitary applications

Sealants for pedestrian walkways for interior use

Fix All High Tack

EN 15651-1:2012: Type F-EXT-INT-CC 20HM

EN 15651-3:2012: Type XS2

EN 15651-4:2012: Type PW-INT

Conditioning: Method B

Test Substrate: aluminium, mortar, glass

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-1:2012 EN 15651-3:2012 EN 15651-4:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10%	
Tensile properties at maintained extension after water immersion	NF	
Microbiological growth	2	
Tensile properties at maintained extension	NF	
Tear resistance	NF	
Tensile properties at maintained extension at -30°C	NF	
Durability	Pass	

UKCA Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Fix All High Tack

Revision: 17-09-2024

Page 5-8

UK Reference nr DOP: 231708UK

Unique identification code of the product-type

Fix All High Tack

Intended use or uses of the construction product

Sealants for facade for interior and exterior applications, intended for use in cold climate

Sealants used for sanitary applications

Sealants for pedestrian walkways for interior use

Name and contact address of the manufacturer as required pursuant to Article 11(5)

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

Authorised representative

Soudal (UK) Ltd, Soudal House, Unit 1, Centurion Way, Centurion Park, Tamworth

B77 5PN Soudal House, Unit 1, Centurion Way, Centurion Park, Tamworth B77 5PN.

System(s) of assessment and verification of consistency of performance of the construction product, as set out in Annex V

System 3: for reaction to fire

System 3: for essential characteristics

Construction product in accordance with applicable designated standards

BS EN 15651-1:2012: Type F-EXT-INT-CC 20HM

BS EN 15651-3:2012: Type XS2

BS EN 15651-4:2012: Type PW-INT

Approved Body

4ward Testing, AB 2538, has carried out Determination of the Product Type under system 3.

Declared Performance: BS EN 15651-1:2012

Essential Characteristics	Performance	Designated Technical Specification
Reaction to fire	E	BS EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Tensile properties at maintained extension after water immersion	NPD	
Tensile properties at break after water immersion	NPD	
Tensile properties at maintained extension at -30°C	NPD	
Durability	Pass	

Conditioning: Method B

Test substrate: aluminium, mortar with primer

Declared Performance: BS EN 15651-3:2012

Essential Characteristics	Performance	Designated Technical Specification
Resistance to flow	≤ 3 mm	BS EN 15651-3:2012
Loss of volume	NPD	
Water and air tightness		
Tensile properties at maintained extension after water immersion	NPD	
Tensile properties at break after water immersion	NPD	
Microbiological growth	NPD	
Durability	Pass	

Conditioning: Method B

Test substrate: aluminium, glass

Declared Performance: BS EN 15651-4:2012

Essential Characteristics	Performance	Designated Technical Specification
Reaction to fire	E	BS EN 15651-4:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Loss of volume	NPD	
Tensile properties at maintained extension	NF	
Tear resistance	NPD	
Durability	Pass	

Conditioning: Method B

Test substrate: mortar with primer, aluminium



The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by

Ing. W. Dierckx
Senior Technical Product Manager
Soudal NV- Belgium

UKCA marking

In accordance with the CPR Regulation (EU) N° 305/2011

Fix All High Tack

**UK
CA**
AB 2538

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium
21

UK Reference nr DOP: 231708UK

BS EN 15651-1:2012
BS EN 15651-3:2012
BS EN 15651-4:2012

Sealants for facade for interior and exterior applications, intended for use in cold climate

Sealants used for sanitary applications

Sealants for pedestrian walkways for interior use

Fix All High Tack

BS EN 15651-1:2012: Type F-EXT-INT-CC 20HM

BS EN 15651-3:2012: Type XS2

BS EN 15651-4:2012: Type PW-INT

Conditioning: Method B

Test substrate: aluminium, mortar with primer

Essential Characteristics	Performance	Designated Technical Specification
Reaction to fire	E	BS EN 15651-1:2012 BS EN 15651-3:2012 BS EN 15651-4:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Tensile properties at maintained extension after water immersion	NPD	
Tensile properties at break after water immersion	NPD	
Microbiological growth	NPD	
Tensile properties at maintained extension	NF	
Tear resistance	NPD	
Tensile properties at maintained extension at -30°C	NPD	
Durability	Pass	