

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Repa-Cryl D

Revision: 25/04/2016

Page 1 from 3

Reference nr DOP: 230744

Unique identification code of the product type:

Soudal Repa-Cryl D

Intended use or uses of the construction product:

Sealant for facade for interior and exterior application.

Construction product in accordance with applicable harmonised specifications:

EN 15651-1:2012: Type F - EXT-INT

System or systems of assesment and verification of consistency of performance of the construction product, as set out in Annex V:

System 3: for essential characteristics

System 3: for reaction to fire

Name and contact address of the manufacturer as required pursuant to Article 11(5):

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

The notified body:

GINGER CEBTP, NB 0074 has carried out Determination of Product Type under system 3.

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Repa-Cryl D

Revision: 25/04/2016

Page 2 from 3

Declared Performance: EN 15651-1:2012

| Essential Characteristics | Performance | Harmonised Technical Specification |
|---|-------------|------------------------------------|
| Reaction to fire | NPD | EN 15651-1:2012 |
| Release dangerous chemicals | NPD | |
| Water and air tightness | | |
| Resistance to flow | ≤ 3 mm | |
| Loss of volume | NPD | |
| Secant modulus at -30°C (N/mm ²) | NPD | |
| Tensile properties at maintained extension at -30°C | NPD | |
| Elongation at break | ≥ 25% | |
| Tensile properties at break after water immersion | ≥ 25% | |
| Durability | Pass | |

Conditioning:

Method A


Test substrate:

Aluminium

Mortar

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Eric van Spreuwel

Technical Product Manager
BE-2300 Turnhout, 25/04/2016

CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Revision: 25/04/2016

Page 3 from 3



NB 0074

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

14

Reference nr DOP: 230744

EN 15651-1: 2012

Sealant for facade for interior and exterior application.

Soudal Repa-Cryl D

EN 15651-1:2012: Type F - EXT-INT

Conditioning:

Method A

Substrate:

Aluminium

Mortar

| Essential Characteristics | Performance | Harmonised Technical Specification |
|---|-------------|------------------------------------|
| Reaction to fire | NPD | EN 15651-1: 2012 |
| Release dangerous chemicals | NPD | |
| Water and air tightness | | |
| Resistance to flow | ≤ 3 mm | |
| Loss of volume | NPD | |
| Secant modulus at -30°C (N/mm ²) | NPD | |
| Tensile properties at maintained extension at -30°C | NPD | |
| Elongation at break | ≥ 25% | |
| Tensile properties at break after water immersion | ≥ 25% | |
| Durability | Pass | |