

Carbon Assembly Paste

Revision: 16/07/2019

Page 1 from 1

Technical data

Basis	Assembly paste with grain structure
Consistency	Stable paste
Application temperature	5 °C → 30 °C

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.

Product description

Carbon Assembly Paste is a specially developed professional assembly paste for carbon parts such as handlebars and seatposts.

Assembly Paste. Wipe away excess product with a cloth.

Health- and Safety Recommendations

Take the usual labour hygiene into account.

Properties

- Increases the friction between carbon parts, as well as aluminum and steel.
- Facilitates assembly and disassembly.
- Granular structure
- Rust and corrosion-resistant
- Eliminates cracking and squeaking.
- Contains no heavy metals.
- Water-repellent

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Applications

- Suitable for the assembly of non-moving parts in carbon, as well as aluminum and steel.
- Applications where the torque can be reduced so that damage can be avoided.

Packaging

Colour: anthracite
Packaging: 200 ml

Shelf life

2 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

Substrates

Nature: rigid, clean, dry, free of dust and grease.

Application method

Application method: Clean and degrease the parts in advance. Apply sufficient Carbon

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.