

Dry Wax

Revision: 16/07/2019

Page 1 from 1

Technical data

Basis	Wax-based
Consistency	Liquid
Density	Ca. 1,02 g/ml
Total solid content	40 %
Acidity level (text)	Ca. 7.8
Drying time	4 h → 5 h
Application temperature	5 °C → 30 °C

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.

Product description

Dry Wax is a specially formulated professional chain lubricant based on wax.

Properties

- Wax containing
- Rust and corrosion-resistant
- Dirt-repellent
- Long lasting protection

Applications

- Suitable for lubrication of bicycle chain, jockey wheels, cassette and chain rings.
- Both for racing and mountain bikes.

Packaging

Colour: white

Packaging: 100 ml

Shelf life

2 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

Substrates

Nature: rigid, clean, dry, free of dust and grease.

Application method

Application method: Degrease and clean chain, jockey wheels, cassette and chain rings thoroughly. Make sure the chain is completely dry. Shake vigorously and then apply Dry Wax to the inside of the chain and at the same time

rotate the chain. Apply enough Dry Wax (2 to 3 layers) and dry the chain before applying the next layer. The chain must be completely dry before cycling. Dirt can be wiped off afterwards from the chain with a dry cloth. Then apply again Dry Wax.

Health- and Safety Recommendations

Take the usual labour hygiene into account.

Remarks

- During heavy rainfall the wax can be washed away.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.