

Lubricant Dry Weather

Revision: 16/07/2019

Page 1 from 1

Technical data

Basis	Synthetic multipurpose EP-oil
Consistency	Fluid
Density	Ca. 0,99 g/ml
Viscosity	Ca. 460 cSt
Flashpoint	Ca. 246 °C
Application temperature	5 °C → 30 °C

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.

Product description

Lubricant Dry Weather is a specially developed professional dry weather chain lubricant based on biodegradable oil.

Weather. Wipe away excess product with a cloth.

Properties

- Reduces friction in moving parts
- Rust and corrosion-resistant
- Reduces friction and wear
- Biodegradable
- Water-repellent
- Does not drip
- Low viscosity, easy to apply.

Health- and Safety Recommendations

Take the usual labour hygiene into account.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Applications

- Suitable for lubrication of bicycle chain, jockey wheels, cassette and chain rings.
- Suitable for dry weather.

Packaging

Colour: transparent

Packaging: 100 ml

Shelf life

2 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

Substrates

Nature: rigid, clean, dry, free of dust and grease.

Application method

Application method: Clean and degrease the parts in advance. Apply sufficient Lubricant Dry

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.